

HOT PRESSURE WASHERS

HG/HD - HOT 2 GO SERIES: V PORTABLE ELECTRIC POWERED, DIESEL FIRED



HG SERIES SHOWN WITH WHEEL KIT



HD SERIES SHOWN WITH WHEEL KIT

HYDRO TEK **PRO**
POWER WASH PERFORMANCE **PRO**

Cleans Fast & Outlasts

www.hydroteksystems.com

HG/HD HOT 2 GO PROLINE SERIES

PORTABLE HOT PRESSURE WASHERS AND STEAM CLEANERS



The Right Power Cleaner, Right Where You Need It!

Common Features

High Intensity Diesel Burners & Super Efficient Heating Coils:

The ultimate balance of power and efficiency in these uniquely designed schedule 80 coils. Provides economical operation with consistent superior performance. Auto ignition adds peace of mind & ease of operation.

Stainless Steel Coil Housing & SS Inner Wrap:

Lifetime corrosion resistance, inside and out – unmatched coil protection, double wall protected to contain the intense heat of the burner providing optimal long life and performance.

Stainless Steel Frames and Panels:

Not just decorative flashes, these rugged and durable panels offer lifetime corrosion resistance and protection of your valuable investment from the harshest environments. Quick connects provide easy removal for full access to all major components and the Ultimate in serviceability.

Other Standard Features:

Adjustable pressure unloader, safety relief valve, burst disc technology and temperature limit switch. Nozzles for various applications, 50' hose, gun and wand included. Heavy duty industrial motor with standard thermal overload protection. NEMA4-Water tight control panel with lighted switches.

HG Series (Hot 2 Go)

Automatic Start-up and Shut-down:

Operator has total control over the system from the trigger gun. This added convenience not only saves time and effort, it reduces wear of the pump, prevents the pump from running dry and produces an energy efficient system. The HG30004E2M, HG22004E2M, HHG15015E1M and HG15002E1M come equipped with the traditional manual On/Off.

4 Gal Fuel Tank with Filtration:

HeavyDuty "roto-molded" rust free fuel tank with in-line fuel filter to protect against contaminated fuel. The 4 gallon fuel tank increases run-times and minimizes refueling during operation.

Downstream Chemical Injection:

The HG series is equipped with downstream chemical injection that can be turned on and off right from the gun – no need for the operator to return to the machine. Chemicals and other additives are introduced after the pump eliminating the risk of pump damage.

HD Series (Hot 2 Go Heavy Duty)

Inlet Chemical Injection:

Inlet soap injection with precision chemical metering valve and float tank injects soap at full pressure for optimal cleaning effectiveness. Panel mounted controls enable the operator to vary the mixture of soap or other additives with ease.

Belt Driven Pump:

High torque, low RPM drive- cooler, quieter, continuous duty performance. These ceramic plunger triplex pumps feature oversized aluminum crankcases with special cooling fins for extended pump life and stainless steel valves, seats, springs and plunger rods for positive seating and increased performance.

7.5 Gal Fuel Tank with Filtration and Adjustable Temperature:

Heavy Duty "roto-molded" rust free fuel tanks with water separating fuel filter to protect against contaminated fuel. Extended run time reduces interruptions. Panel mounted adjustable temperature knob with steam setting increases cleaning effectiveness.



HG SERIES



HD SERIES

Specifications

Model	PSI	GPM	Temp.	HP	Voltage
HG SERIES					
HG15015E1M	1500	1.5	200 F	1.5	115v - 1ph 15a
HG15002E1M	1500	2	200 F	2	115v - 1ph 20a
HG22004E2M	2200	3.5	200 F	5.0	208/230v - 1ph
HG30004E2M	2900	3.5	200 F	6.5	230v - 1 ph 30a
HD SERIES					
HG15015E1H	1500	1.5	200 F	1.5	115v - 1ph 15a
HG15002E1C	1500	2	200 F	2	115v - 1ph 20a
HG22004E2C	2200	3.5	200 F	5	208/230v - 1ph
HD SERIES					
HD10003E1H	1000	2.8	250 F	2	115v - 1ph 20a
HD20004E2H	2000	3.5	250 F	5	208/230v - 1ph
HD25004E2H	2500	3.6	250 F	6.5	230v - 1ph
HD25004E2C	2500	3.6	250 F	6.5	230v - 1ph
HD30003E2H	3000	3	250 F	6.5	230v - 1ph

Optional Accessories...

Wet sandblast assembly, Hose and wand extensions, Wheel kits and stainless steel hose reels.

Specifications may vary, consult factory for custom models

DISTRIBUTED BY:



10418 Enterprise Drive Redlands CA 92374

Toll Free: (800) 274-9376 Fax: (909) 799-9888 www.hydroteksystems.com

HGHD PROLINE 5/05 Printed in the USA © 2005.