

HOT/COLD PRESSURE WASHER: NATURAL GAS / LP FIRED, ELECTRIC POWERED

The **HN Pro Line™ Series** is a heavy-duty stationary unit offering high output and instant cleaning power with adjustable temperature for various cleaning applications. The Stainless Steel enclosure offers lifetime corrosion resistance and accessibly to components. High torque / low RPM belt driven pump ensures years of worry free service with built in overheat protection if machine is left on. The automatic electronic ignition eliminates the need to manually light a pilot and increases the safety of the machine.

TECHNICAL DATA	HN20004E2C /E8C	HN20005E2H	HN30005E3H /E8H	HN30005E4H
PRESSURE	2000	2000	3000	3000
FLOW CAPACITY	3.8	4.8	4.8	4.8
OUTLET TEMP	Adjustable to 250°F (130°F Rise)			
MOTOR	5.0 hp	6.5 hp	10 hp	10 hp
VOLTS – PHASE AMP DRAW	E2C=230v 1ph 22a E8C=208v 1ph 22a	230v 1ph 27amp	E3H=230v 3ph 27a E8H=208v 3ph 30a	460v 3ph 14amp
CONTROLS	Rocker switches w/diagnostic lights, thermal overload protection, NEMA 4 electrical box			
POWER DRIVE	V-Belt Drive with Integrated Tension Adjustment			
PUMP	Cat Triplex Plunger	AR Triplex Ceramic Plunger		
WATER SUPPLY	3 ½ Gallon Float Tank with Double Filtration and Back Flow Prevention			
PRES. CONTROL	K-7 Total Relief with <i>By-Pass-Cool</i> System / Safety Relief Valve and Burst Disc			
PRESSURE HOSE	3/8 x 50' Steel Wire Braided / 250°F 3000psi Rated			
GUN / WAND	Insulated Shut Off Gun with 36" Wand			
SOAP INJECTION	Full Pressure Chemical Injection, Precision Stainless Steel Metering Valve			
NOZZLES	#5.5 0°, 15°, 40°, Steam	#6.5 0°, 15°, 40°, Steam	#5.5 0°, 15°, 40°, Steam	#5.5 0°, 15°, 40°, Steam
BURNER COIL	½" x 220' Schedule 80, 7 Pancake, Ceramic Insulation and Stainless Steel Wrap and Cap			
BURNER	Natural Gas with Auto Ignition and 90 Second Safety Lockout, Cast Iron Ring, Brass Jets			
BURNER INPUT	360,000 BTU	440,000 BTU	440,000 BTU	440,000 BTU
WEIGHT/DIM	475#, 47x48x24	477#, 47x48x24	492#, 47x48x24	500#, 47x48x24

*Specifications subject to change without notification and may vary due to ambient conditions.



Featuring:

- ✓ **Stainless Steel** "Flip Open" cover provides exceptional access to pump and all components for the best serviceability in its class. Frame includes 12 ga. legs.
- ✓ **Adjustable Thermostat** with Steam Setting for various cleaning applications
- ✓ **By-Pass-Cool** System protects pump from overheating if left on after use
- ✓ **24 Volt Automatic Ignition** system on low emission natural gas burner

Options...

Hose Reel (AR008, AR178, AR179) Draft Diverter (BGD10), LP Conversion Kit (BGV05), Wheel Kit for LP model (AHB12)

TO: _____

COMMENTS: _____

YOUR PRICE: _____

DISTRIBUTED BY: _____

