

### Pro Tow Wash® • TRANSPORT TRAILER WITH 540 GALLON TANK

The T500 tandem axle trailer, with your choice of pressure washer, is a fully integrated self-contained pressure washing system. The two 270 Gallon water tanks with integrated baffling provide 540 Gallons of water supply & ample cleaning power to sustain most remote-cleaning requirements. The dual water tanks provide flexibility for operation and can be either plumbed together or maintained separate. The unique torsion axle suspension provides the smoothest ride available and prevents damage to the pressure washer from a harsh ride. The enhanced wheel travel (up to 300% over conventional trailers) keeps road vibration and rattle to a minimum. Long life, rugged, durable and dependable service – engineered into the T500 Series Pro Tow Wash® Trailers

TECHNICAL DATA	T500EE	T500S
MACHINE CAPACITY	SS and SC Series (up to 1100 pounds total)	
SUSPENSION / AXLE	Two 3700# Torsion Axles-Up to 300% more wheel travel over conventional trailers 7500# GVWR	
TRAILER BRAKES	10x2 Electric Brakes, Breakaway Switch	10x2 Surge Brake – Rear Axle
WHEEL / TIRE	4 - 14" White Spoke Rim, 5 Lug, ST205/75D/14 Tires, 1760# capacity per tire @ 35psi	
COUPLER / TONGUE	2 5/16" Ball Coupler, Adjustable Height, Dual 3/8" Safety Chains	
TOW REQUIREMENT	2 5/16 Ball, 7500 Pound Rated, Class IV	
FENDERS	12 GA Steel Fender with recessed tail light mount	
LIGHTS	Peterson Rubber Grommet Snap-In, 4 Pole Flat Wiring Connector, Dot Approved	
JACK	Bolt-On Swing Up Jack 1500# Capacity With Large Swivel Caster 8" Diameter	
WATER TANK	540 Gal. total capacity (dual 270 gal) seamless polyethylene, 8" lid, garden hose fill fitting	
WATER SUPPLY	¾" 80 Mesh Strainer with Drain, Self Clean Filter Valve	
CHASSIS CONSTRUCTION	12 GA Steel Frame with Structural Tube Spine, Powder Coat Wrinkle Finish	
NET WEIGHT / DIMENSIONS	1163 Lbs. Empty (No Machine) 168" Long x 70" Wide x 61" High	

\*Specifications subject to change without notification and may vary due to ambient conditions.

**Note: Shipped to distributors only, not available to drop ship**

\* Trailers with electric brakes must include a battery power source. We recommend installing a pressure washer equipped with a battery.

#### Featuring:

- ✓ **Rugged Fender:** Can be used as a step for tank access, will not bend, supports tank.
- ✓ **Recessed Tail Lights:** Will not break off, rubber isolates to reduce bulb failure.
- ✓ **Storage Areas:** Integrated areas for chemical, wand & tools. – Also protects hose on reels.
- ✓ **Stainless Exhaust Pipe Extension:** Lifetime corrosion resistance insures no need to replace in a few years.
- ✓ **Inlet Plumbing:** System Engineered to prevent pump damage caused by cavitations & contamination
- ✓ **Reel Extension:** Integrated hose reel mounts for optional indexing reels

#### Options...

**AR180** Discharge Hose Reel High Pressure 150ft max (Curb side), **AR181** High Pressure 150ft max (Street side) **AR182** Inlet Hose Reel Low Pressure 100ft max (Street side) **AR191** High Pressure 300ft of 3/8 hose, **AR192** Low Pressure 200 ft of 5/8 hose, **HLB98** Light Bar Option

TO: \_\_\_\_\_

COMMENTS: \_\_\_\_\_

YOUR PRICE: \_\_\_\_\_

DISTRIBUTED BY: \_\_\_\_\_



Shown with Optional Light Bar & Hose Reels  
 Pressure washer not included